

HazMat Chemical Storage

Buildings are specifically designed for outdoor storage and dispensing from 55-gallon drums containing flammable or combustible liquids. Outer wall is constructed of welded 16 or 12-gauge steel. Inner wall is constructed of 20-gauge steel. Outdoor storage buildings are engineered with 3" airspace throughout and come standard with a commercial grade lockset handle.

All models are designed in accordance with the standards set forth by NFPA Code 30 and comply with OSHA and EPA regulations. All models are FM approved for the storing and dispensing of flammable and combustible liquids. Standard color is Gray.

LOCKERS/BUILDINGS FOR STORING 55-GALLON DRUMS - outdoor and indoor application

								Fire Rating Upgrade			
								Two-Hour Fire Rating		Four-Hour Fire Rating	
Model No.	Test Lab Approv.	Sump Capacity to Hold	Sump Capacity	Exterior Dim. H x W x D			Approx. Ship Wt.	Model No.	Approx. Ship Wt.	Model No.	Approx. Ship Wt.
B200	FM*	2 55-Gal. Drums	55 Gal.	7'	5'	3'6"	1,281 lbs.	OPFR2-200	1,298 lbs.	OPFR4-200	1,722 lbs.
B400	FM*	4 55-Gal. Drums	68	7'	5'	5'	1,748	OPFR2-400	1,363	OPFR4-400	1,878
B600	FM*	6 55-Gal. Drums	102	8'4"	7'	5'	2,061	OPFR2-600	2,239	OPFR4-600	2,973
B900	FM*	9 55-Gal. Drums	154	8'4"	7'	7'	2,567	OPFR2-900	2,712	OPFR4-900	3,604
B1200	FM*	12 55-Gal. Drums	206	8'4"	7'	9'	3,200	OPFR2-1200	3,059	OPFR4-1200	4,108
* B1600	* FM*	16 55-Gal. Drums	272	8'4"	10'	8'	5,515	OPFR2-1600	3,253	OPFR4-1600	3,869
* B2400	* FM*	24 55-Gal. Drums	393	8'4"	14'	8'	6,994	OPFR2-2400	3,600	OPFR4-2400	5,107
* B3200	* FM*	32 55-Gal. Drums	514	8'4"	18'	8'	8,652	OPFR2-3200	4,356	OPFR4-3200	6,194
* B4800	* FM*	48 55-Gal. Drums	757	8'4"	26'	8'	9,963	OPFR2-4800	7,823	OPFR4-4800	10,322
* B6400	* FM*	64 55-Gal. Drums	1,000	8'4"	34'	8'	12,851	OPFR2-6400	9,616	OPFR4-6400	12,777
* B8000	* FM*	80 55-Gal. Drums	1,243	8'4"	42'	8'	15,369	OPFR2-8000	11,737	OPFR4-8000	15,537

*Sizes 1600 and larger are constructed of 12-gauge Galvannealed Steel



Industry's 1st and Only
FM Approved Fire
Rated Wall & Roof
Design Tested at
Intertek Testing
Laboratories



Intertek

Model #B200

EXPLOSION RELIEF PANEL

Model No.	Description
OXRP-200	1- 48" x 60"
OXRP-400	1- 48" x 60"
OXRP-600	1- 24" x 60" and 1- 48" x 60"
OXRP-900	1- 24" x 60" and 1- 48" x 60"
OXRP-1200	2- 48" x 60"
OXRP-1600	2- 48" x 60"
OXRP-2400	1- 24" x 60" and 2- 48" x 60"
OXRP-3200	3- 48" x 60"
OXRP-4800	4- 48" x 60"
OXRP-6400	5- 48" x 60"
OXRP-8000	6- 48" x 60"

Securall® Fire-Rated Storage Buildings carry the Factory Mutual System Approval label and have an FM Approved Fire Rated Wall & Roof Design. Wall and Roof are Tested at Intertek Testing Laboratories. Securall® Fire-Rated Storage Buildings constructed based upon UL Fire Resistance Ratings classification criteria. Standard models are available with a 2-hour and 4-hour fire ratings upgrade. Wall ratings are either 2 or 4 hour fire rated. Roof ratings are either 1.5 or 3 hour fire rated (Check with your local authority having jurisdiction for correct wall/roof rating needed).




★ **Model #B1600**
shown with options and ramp

CUSTOM & SPECIAL OPTIONS call 888-326-7890 or Email info@harsco.com



Fire Suppression System




Interior Shelving



Explosion Proof Lighting



Explosion Proof Heater



Explosion proof Air Conditioner

* Complies with OSHA Regulations

FM Factory Mutual Tested and Approved

~ Designed in Accordance with Specifications set forth by the National Fire Protection Association

★ Best Seller!